


AQUAFLEX

PRIMER W



Water based primer

DESCRIPTION

Aquaflex Primer W is a single component water based acrylic coating used to penetrate and prime concrete and masonry surfaces. When dry, it is resistant to water.

Aquaflex Primer W is suitable as a primer prior to the application of water based membranes in internal/external applications. It is a water based acrylic system, which creates a positive bond between the substrate and most water based coatings.

Aquaflex Primer W can be used over the top of most acrylic coatings.

TYPICAL APPLICATION

- New and old concrete
 - Compressed fibro
 - Timber
 - Primer for acrylic coatings
-

SURFACE PREPARATION

Surface must be structurally sound with loose or flaking material removed by suitable means before **Aquaflex® PRIMER W** can be applied. Surface deformities should be filled with a commercial filling compound in accordance with the manufacturers specifications.

APPLICATION REQUIREMENTS

Surfaces to be waterproofed should be clean, dry and free from oils, grease and other contaminants. Application is with a brush, long nap roller or conventional spray. Ensure that the coating is applied evenly at the recommended coverage rates.

Curing time is approximately 1 hour.

COVERAGE

Application rate of 5-8 sqm/ltr on vertical and horizontal surfaces.

CLEAN UP

Clean all equipment in fresh water immediately after use.

AQUAFLEX

PRIMER W

technical data sheet

CLEAN UP

Clean all equipment in fresh water immediately after use.

PACKAGING

Container Size 20 litres plastic pails

Shelf Life 1 year in unopened containers store at 20°C

SAFETY

Avoid contact with skin and avoid breathing vapour. Provide adequate ventilation. Keep out of reach of children, If swallowed contact a doctor or Poisons Information Centre.

PRECAUTIONS

Area subject to rising damp should be primed with **Aquaflex® water based epoxy**. Do not apply above 32°C or below 8°C. Protect membrane against damage before and during backfilling or tiling etc. Do not use solvent based adhesives or sealers.
