


AQUAFLEX

Fibre Plus



Water based fibre

IDENTIFICATION

Product Name:	Aquaflex® Fibre plus
Other Names:	Pigmented, Acrylic Emulsion
UN Number:	Exempt
Dangerous goods Class and Subsidiary Risk:	Non Hazardous
Hazhem Code:	N/A
Poison Schedule Number:	N/A
Use:	Waterproof Membrane Coating

PHYSICAL DESCRIPTION/ PROPERTIES

Appearance:	Grey Viscous Liquid
Boiling Point:	100°C
Specific Gravity:	1.26kg/l
Flashpoint:	N/A
Flammability Limits:	N/A
Solubility in Water:	Miscible

INGREDIENTS

Chemical Name	CAS Number	Proportion
Latex Emulsion		10%-50%
Calcium Carbonate	Not Est.	>60%
Silicone Dioxide	471-34-1	10-60%
Titanium Dioxide	14808-60-7	10-60%
Additives	13463-67-7	<10%
	Not Est.	>10%
Non Hazardous Ingredients	Balance	

AQUAFLEX

FLOSEAL EPOXY VAPOURLOCK

HEALTH HAZARD (Health Effects and First Aid)

- If Swallowed: Slightly toxic. Do not induce vomiting, give a glass of water to drink and seek medical advice.
- Eye Contact: Irritant. Remove Contact lense. Wash eyes with plenty of fresh water. Seek medical care if irritant persists.
- Skin: Irritant. Thoroughly wash exposed area with soap and water. Do not use solvents to remove material.
- Inhaled: Slightly irritant to susceptible individuals. Remove to fresh air. Apply artificial resuscitation if necessary.
- Advice to doctor: Treat systematically.
-

PRECAUTIONS FOR USE

- Exposure Standards: Low toxicity, low irritant
- Engineering Controls: Ventilate if in a confined space
- Personal Protection: PVC gloves, safety glasses
- Flammability: Non flammable
-

SAFE HANDLING

- Storage and Transport:
Store in cool place. Avoid Freezing.
- Spills and Disposal:
Absorb spills with dry earth or sand. Dispose as solid waste.
- Fire/Explosion Hazard:
No fire or explosion hazard exists.