


AQUAFLEX PRIMER W



Water based primer

SAFETY DATA SHEET

IDENTIFICATION

Product Name:	Aquaflex® PRIMER W
Other Names:	Pigmented Acrylic Emulsion
UN Number:	Exempt
Dangerous goods Class and Subsidiary Risk:	Non hazardous
Hazhem Code:	Exempt
Poison Schedule Number:	Exempt
Use:	Acrylic Primer

PHYSICAL DESCRIPTION/ PROPERTIES

Appearance:	White Viscous Liquid
Boiling Point:	100°C
Vapour Pressure:	30mm of Hg, 25°C
Specific Gravity:	1.00
Flashpoint:	N/A
Flammability Limits:	N/A
Solubility in Water:	Miscible

INGREDIENTS

Chemical Name	CAS Number	Proportion
Acrylic Emulsion	Not Est.	> 60%
Additives	Not Est.	< 10%

AQUAFLEX

PRIMER W

HEALTH HAZARD (Health Effects and First Aid)

If Swallowed:	Mild irritation. Give water to drink. Do not induce vomiting. Seek Medical advice
Eye Contact:	Irritant. Remove Contact lense. Wash eyes with plenty of fresh water. Seek medical care if irritant persists.
Skin:	Irritant. Thoroughly wash exposed area with soap and water.
Inhaled:	Not hazardous. Provide adequate fresh air.
Advice to doctor:	Treat systematically.

PRECAUTIONS FOR USE

Exposure Standards:	Low toxicity, low irritant
Engineering Controls:	Ventilate confined spaces
Personal Protection:	PVC gloves and safety glasses
Flammability:	Non flammable

SAFE HANDLING

Storage and Transport:

Store in cool place. Avoid Freezing.

Spills and Disposal:

Absorb spills with dry earth or sand. Dispose as solid waste.

Fire/Explosion Hazard:

No fire or explosion hazard exists.