


AQUAFLEX

PU Under Tile



Polyurethane non exposed (under Tile) membrane

SAFETY DATA SHEET

IDENTIFICATION

Product Name:	Aquaflex® PU
Other Names:	Moisture Cured Polyurethane
UN Number:	Exempt
Dangerous goods Class and Subsidiary Risk:	Non Hazardous
Hazhem Code:	Exempt
Poison Schedule Number:	Exempt
Use:	Waterproof Membrane Coating

PHYSICAL DESCRIPTION/ PROPERTIES

Appearance:	Grey or Green Viscous Liquid
Boiling Point:	100°C
Vapour Pressure:	30mm of Hg, 25°C
Specific Gravity:	1.26
Flashpoint:	N/A
Flammability Limits:	N/A
Solubility in Water:	Miscible

INGREDIENTS

Chemical Name	CAS Number	Proportion
Urethane Prepolymer	Not Est.	90%
Aromatic 150	64742-95-6	10%

AQUAFLEX

PU Under Tile

HEALTH HAZARD (Health Effects and First Aid)

- If Swallowed: Mild irritation. Give water to drink. Do not induce vomiting. Seek medical advice
- Eye Contact: Irritant. Remove contact lense. Wash eyes with plenty of fresh water. Seek medical care if irritant persists.
- Skin: Irritant. Thoroughly wash exposed area with soap and water.
- Inhaled: Not hazardous. Provide adequate fresh air.
- Advice to doctor: Treat systematically

PRECAUTIONS FOR USE

- | | |
|-----------------------|-------------------------------|
| Exposure Standards: | Low toxicity, low irritant |
| Engineering Controls: | Ventilate confined spaces |
| Personal Protection: | PVC gloves and safety glasses |
| Flammability: | Non flammable |

SAFE HANDLING

- Storage and Transport:
Store in cool place. Avoid Freezing.
- Spills and Disposal:
Absorb spills with dry earth or sand. Dispose as solid waste.
- Fire/Explosion Hazard:
No fire or explosion hazard exists.